

TECHNICAL DATA SHEET

SL-907 UNIVERSAL ACRYLIC GAP SEALANT - ECONOMICAL GRADE

DESCRIPTIONS:

SILOCK SL-907 UNIVERSAL ACRYLIC GAP SEALANT – ECONOMICAL GRADE IS A SINGLE COMPONENT, PAINTABLE AND LATEX EMULSION BASED ACRYLIC SEALANT. IT IS SUITABLE FOR SEALING OF GAPS AND CURES TO A FLEXIBLE JOINT. IT HAS A GOOD ADHESION TO A VARIETY OF POROUS SURFACES SUCH AS WOOD, CONCRETE, NATURAL STONE, ETC WITHOUT PRIMER. IT CAN BE EASILY CLEANED UP WITH WATER.

FEATURES:

- ◆ MORE HARDER
- ◆ SINGLE COMPONENT
- ◆ PAINTABLE
- ◆ FLEXIBLE
- ◆ ECONOMY
- ◆ CAN BE CLEANED UP WITH WATER
- ◆ EXCELLENT GUNNABILITY
- ◆ GOOD WEATHERABILITY

USES:

- ◆ IT ADHERES TO A VARIETY OF POROUS SUBSTRATES SUCH AS WOOD, CONCRETE, NATURAL STONE ETC WITHOUT PRIMER.

WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS

NOT RECOMMENDED FOR:

IT SHOULD NOT BE APPLIED OUTDOORS IF IT IS LIKELY TO BE RAINED UPON WITHIN 2 HOURS OF APPLICATION.

NOT FOR: USE IN AREAS OF CONSTANT WATER IMMERSION.

NOT FOR: JOINT MOVEMENT MORE THAN 10%.

COLOUR:

WHITE. OTHER COLOURS ARE AVAILABLE UPON REQUEST.

APPLICATIONS:

- ◆ SURFACE MUST BE CLEAN AND DRY.
- ◆ MASK SMOOTH SURFACE TO SIMPLIFY CLEAN UP.
- ◆ USE APPROVED BACK-UP MATERIAL IN JOINT.
- ◆ CUT NOZZLE TO DESIRED SIZE.
- ◆ INSERT CARTRIDGE INTO CAULKING GUN.
- ◆ PUSH SEALANT AHEAD FOR UNIFORM BEAD.
- ◆ TOOL WITHIN 5 MINUTES.
- ◆ CLEAN OFF EXCESS SEALANT WITH WATER.

TECHNICAL DATA SHEET



SL-907 UNIVERSAL ACRYLIC GAP SEALANT - ECONOMICAL GRADE

CURING TIME:

SL-907 WILL TACK FREE IN APPROXIMATELY 10 MINUTES AND WILL CURE TO A DEPTH OF 10MM IN 7-14 DAYS. LONGER CURING TIME MAY BE NECESSARY IN COLD AND HIGH HUMIDITY AREA.

SPECIFICATIONS:

BASE	ACRYLIC LATEX
APPEARANCE	NON-SAGGING PASTE
COLOUR	WHITE
SPECIFIC GRAVITY	1.65 ± 0.05
SHORE A HARDNESS	40 APPROX.
SOLID CONTENTS	85 ± 3 %
TACK FREE TIME	10 MINUTES APPROX.
APPLICATION TEMP.	5°C TO 50°C
SERVICE TEMP.	-10°C TO 80°C
SHELF LIFE	12 MONTHS

STORAGE:

MATERIAL SHOULD BE STORED IN A DRY AND COOL PLACE BETWEEN +5°C TO +30°C.

CAUTION:

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET OF THIS PRODUCT BEFORE HANDLING OR USING.

THIS INFORMATION IS PROVIDED IN GOOD FAITH AND IS BELIEVED ACCURATE BASED ON A REVIEW OF CURRENT COMPOSITION AND INFORMATION SUPPLIED BY VENDORS. NO WARRANTY IS EXPRESSED OR IMPLIED. LIABILITY IS EXPRESSLY DISCLAIMED.

SILOCK®
PROFESSIONAL
SOLUTION