



REV : 02

DATE : 15th Aug 2018

TECHNICAL DATA SHEET



SL-50 CARB & CHOKE / FUEL INJECTION CLEANER

DESCRIPTIONS:

SILOCK SL-50 CARB & CHOKE / FUEL INJECTION CLEANER ABLE TO REMOVE GREASY DIRT, GUM AND CARBON DEPOSITS ON PVC VALVE, ERG VALVE, CHOKE AND OTHER PARTS EFFECTIVELY. IT IS EASILY AND FAST TO FLUSH OFF THE CHARCOAL RESIDUE ON CARBURETOR WITH ITS SPRAY TUBE. CARBURETOR CLEANER CAN ENHANCE COMBUSTION DEFICIENCY, GOOD OF SAVE OIL AND DECREASE THE GAS POLLUTION.

APPLICATIONS:

- WITH ENGINE COLD AND OFF REMOVE AIR FILTER.
- ◆ SPRAY CARBURETOR CLEANER ONE EXTERIOR ON THE SURFACE OF CARBURETOR.
- ♦ AFTER CARBURETOR DRIES, PLACE THE TRANSMISSION INTO "PARK", SET EMERGENCY BRAKE AND THEN START THE ENGINE.
- ♦ DO NOT USE PRODUCT IF ENGINE IS BACKFIRING.
- SPRAY THE PRODUCT IN SHORT BURSTS AROUND THE INSIDE OF THE CARBURETOR WHILE SLIGHTLY REVVING THE ENGINE.

SPECIFICATIONS:

FORM CLEAR, LIGHT TAN LIQUID WITH SOLVENT ODOUR

COLOUR LIGHT TAN SPECIFIC GRAVITY 0.85 ± 0.05 BOILING POINT 205 °C VOLATILE 100%

INNER PRESSURE 0.45 – 0.60 MPA

CAUTION:

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET OF THIS PRODUCT BEFORE HANDLING OR USING.

THIS INFORMATION IS PROVIDED IN GOOD FAITH AND IS BELIEVED ACCURATE BASED ON A REVIEW OF CURRENT COMPOSITION AND INFORMATION SUPPLIED BY VENDORS. NO WARRANTY IS EXPRESSED OR IMPLIED. LIABILITY IS EXPRESSLY DISCLAIMED.