

## TECHNICAL DATA SHEET



### SUPER GLUE

#### DESCRIPTIONS:

**SILOCK SUPER GLUE** IS A CYNOACRYLATE ADHESIVE THAT SET WITHIN SECONDS TO FORM A STRONG BOND ON MOST OF THE SMOOTH SURFACE. IT WORKS WELL ON BOTH POROUS AND NON-POROUS MATERIALS. THE ADHESIVE CAN BE USE TO BOND MOST OF THE METAL, WOOD, RUBBERS, PLASTICS, LEATHER, CERAMICS, GLASS AND FABRIC.

#### FEATURES:

- ◆ EASY TO APPLY.
- ◆ FAST SETTING WITHIN SECONDS.
- ◆ STRONG BONDING STRENGTH, ESPECIALLY ON SMOOTH SURFACE WITHOUT GAP.
- ◆ COST SAVING.

#### USES:

BONDING MOST OF THE METALS, WOOD, RUBBERS, PLASTICS, LEATHER, CERAMICS, GLASS AND FABRIC.

***WE RECOMMEND PRELIMINARY COMPATIBLTY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS***

#### NOT RECOMMENDED FOR:

NOT USE FOR: AREAS OF CONSTANT WATER IMMERSION.  
NOT FOR: PE, PP, PTFE AND BITUMINOUS SURFACE.

#### APPLICATIONS:

- ◆ SURFACE MUST BE CLEAN, DRY AND FREE FROM GREASE AND OLD GLUE.
- ◆ MASK SMOOTH SURFACE TO SIMPLIFY CLEAN UP.
- ◆ APPLY TO ONE SURFACE ONLY.
- ◆ APPLY SUITABLE PRESSURE ON BONDING SUBSTRATES.
- ◆ CLEAN OFF EXCESS ADHESIVE WITH ACETONE.

#### CURING TIME:

CONTACT ADHESIVE WILL BOND IN APPROXIMATELY 30 - 45 SECONDS UNDER ROOM TEMPERATURE.

#### SPECIFICATIONS:

APPEARANCE	CLEAR LIQUID.
ODOUR	PUNGENT SMELL.
SPECIFIC GRAVITY	1.05 ± 0.05
VISCOSITY	100 CPS APPROX.
APPLICATION TEMP.	-10°C TO 40°C
SERVICE TEMPERATURE	-10°C TO 60°C
SHELF LIFE	6 MONTHS @ 20°C

#### STORAGE:

MATERIAL SHOULD BE STORED IN A DRY AND COOL PLACE BELOW +20°C.

## TECHNICAL DATA SHEET



### SUPER GLUE

**CAUTION:**

SUPER GLUE BONDS SKIN AND EYES IN SECONDS. READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET OF THIS PRODUCT BEFORE HANDLING OR USING.

*THIS INFORMATION IS PROVIDED IN GOOD FAITH AND IS BELIEVED ACCURATE BASED ON A REVIEW OF CURRENT COMPOSITION AND INFORMATION SUPPLIED BY VENDORS. NO WARRANTY IS EXPRESSED OR IMPLIED. LIABILITY IS EXPRESSLY DISCLAIMED.*

**SILOCK®**  
PROFESSIONAL  
SOLUTION