

TECHNICAL DATA SHEET

SILOCK® SL-930 AWNING & ROOFING SEALANT

DESCRIPTIONS:

SILOCK SL-930 AWNING & ROOFING SEALANT IS ONE PART SEALANT THAT OFFER EXCELLENT ADHESION, OUTSTANDING DURABILITY AND EXCELLENT GUNNABILITY FOR GENERAL SEALING APPLICATION.

FEATURES:

- ◆ OUTSTANDING DURABILITY
- ◆ ONE PART NO MIXING
- ◆ LOW VOC (VOLATILE ORGANIC COMPOUND)
- ◆ FLEXIBLE ($\pm 3\%$)
- ◆ EXCELLENT GUNNABILITY (-20°C TO 50°C)
- ◆ WEATHER PROOF
- ◆ LOW SHRINKAGE
- ◆ NO SAGGING
- ◆ PRIMERLESS ADHESION TO MOST MATERIALS
- ◆ PAINTABLE AFTER CURED

USES:

GENERAL JOINT SEALING IN EXTERNAL WALLING, WINDOW AND DOOR FRAMES, ROOFS AND OTHERS.

WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS

NOT RECOMMENDED FOR:

MULTIPURPOSE AWNING CAULK IS NOT SUITABLE FOR HIGH JOINT MOVEMENT SUBSTRATE (MORE THAN $\pm 3\%$ JOINT MOVEMENT).

COLOUR:

WHITE, GREY AND BLACK. OTHER COLOURS ARE AVAILABLE UPON REQUEST

APPLICATIONS:

- ◆ SURFACE MUST BE CLEAN AND DRY.
- ◆ MASK SMOOTH SURFACE TO SIMPLIFY CLEAN UP.
- ◆ USE APPROVED BACK-UP MATERIAL IN JOINT.
- ◆ CUT NOZZLE TO DESIRED SIZE.
- ◆ INSERT CARTRIDGE INTO CAULKING GUN.
- ◆ PUSH SEALANT AHEAD FOR UNIFORM BEAD.
- ◆ TOOL WITHIN 10 MINUTES.
- ◆ CLEAN OFF EXCESS SEALANT WITH MINERAL SPIRIT.

CURING TIME:

MULTIPURPOSE AWNING CAULK WILL TACK FREE IN APPROXIMATELY 24 HOURS.

REV : 02
DATE : 15th Aug 2018

TECHNICAL DATA SHEET



SL-930 AWNING & ROOFING SEALANT

SPECIFICATIONS:

CURING SYSTEM	OXIDIZING
APPEARANCE	NON-SAGGING PASTE
ODOUR	OLEO-RESINOUS
SPECIFIC GRAVITY	1.60 ± 0.10
MAX. JOINT MOVEMENT	± 3%
SHRINKAGE	5 % APPROX.
TACK FREE TIME	24 HOURS APPROX.
APPLICATION TEMP.	4°C TO 50°C
SERVICE TEMP.	-5°C TO 60°C
SHELF LIFE	12 MONTHS

STORAGE:

MATERIAL SHOULD BE STORED IN A DRY AND COOL PLACE BETWEEN +5°C TO +30°C.

CAUTION:

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET OF THIS PRODUCT BEFORE HANDLING OR USING.

THIS INFORMATION IS PROVIDED IN GOOD FAITH AND IS BELIEVED ACCURATE BASED ON A REVIEW OF CURRENT COMPOSITION AND INFORMATION SUPPLIED BY VENDORS. NO WARRANTY IS EXPRESSED OR IMPLIED. LIABILITY IS EXPRESSLY DISCLAIMED.

SILOCK®
PROFESSIONAL
SOLUTION